



- GENERAL NOTES:**
- a.) REFER TO BOM LIST WHEN ORDERING PARTS.
 - b.) REFER TO CARE & OPERATION MANUAL FOR ADDITIONAL INFO.
 - c.) A SUPPORT PLATE MUST BE USED.
 - d.) DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.

INCH
 ø0.531 THRU
 16 HOLES
 EQUALLY SPACED

INCH
 ø0.656 THRU
 12 HOLES
 EQUALLY SPACED

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS		WEIGHT	WIR	FIRST USE	MATERIAL	HEAT TREAT	DATE	TWIN DISC INCORPORATED RACINE, WI 53403 - USA			
MACHINED DIMENSIONS X ±0.25 XX ±0.13 XXX ±0.13 ALL ANGULAR TOLERANCES ±1° GEOMETRIC TOLERANCING PER ASME Y14.5M 1994		kg	N.m	ASSY. SP218P008 MODEL SP218DP0	SIMILAR TO SP218P005	NAME SP218DP0 POWER TAKE OFF	11-02-04				
NOTICE: THIS PRINT CONTAINS PROPRIETARY INFORMATION AND IS NOT TO BE USED IN ANY MANNER RETRIBUTAL TO THE INTEREST OF TWIN DISC. INCORPORATE THIS NOTICE IS NOT INTENDED TO WAIVE OR LIMIT RIGHTS GRANTED TO THE U.S. GOVERNMENT OR OTHERS BY CONTRACT.								SCALE: 25 = 1 DRN DJH CRK JTS RPPD JTS	DWG SIZE A1	SHT. 2 OF 2	REV A